

## AGRIMAX RT 955 - Technical Specifications



### Description

AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying and vineyards. The special tread design with a rounded shoulder provides excellent traction performance, stability and self-cleaning properties. Thanks to its strong casing, AGRIMAX RT 955 has a high load capacity.

### UM

International Standard

### Construction



RADIAL

### Machinery

Agriculture: Sprayer • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	210/95 R 28 (8.3 R 28)
LI/SS	116 A8/B

## Dimensions International Standard

Section Width (mm)	214
Overall Diameter (mm)	1111
Static Loaded Radius (mm)	513
Rolling Circumference (mm)	3364
SRI (mm)	525
Rim Rec	W 7
Rim Alt	W 6
ECE	E4-106R-001819
TRA Code	R1

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8
50	590	675	775	875	975	1075	1165	1250	-
40	590	675	775	875	975	1075	1165	1250	-
30	630	725	835	940	1050	1155	1250	1340	-
10	865	995	1110	1220	1350	1485	1725	1820	1875

Printed on 5/2/2024 2:48 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..