

# AGRIMAX RT 955 - Technical Specifications



## Description

AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying and vineyards. The special tread design with a rounded shoulder provides excellent traction performance, stability and self-cleaning properties. Thanks to its strong casing, AGRIMAX RT 955 has a high load capacity.

## UM

US Standard

## Construction

 RADIAL

## Machinery

Agriculture: Sprayer • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	210/95 R 44 (8.3 R 44)
LI/SS	120 A8/B

## Dimensions US Standard

Usa code	94042760
Section Width (inch)	8.4
Overall Diameter (inch)	59.8
Static Loaded Radius (inch)	28.4
Rolling Circumference (inch)	183.2
Rim Rec	W 7
Rim Alt	W 6
ECE	E4-106R-000771
TRA Code	R1

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35	41
30	1450	1680	1920	2160	2410	2660	2880	3090	-
25	1450	1680	1920	2160	2410	2660	2880	3090	-
20	1550	1790	2050	2310	2580	2840	3080	3310	-
5	2140	2460	2730	3010	3340	3660	4270	4500	4630

Printed on 12/6/2023 3:28 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..