

AGRIMAX RT 955 - Technical Specifications



Description

AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying and vineyards. The special tread design with a rounded shoulder provides excellent traction performance, stability and self-cleaning properties. Thanks to its strong casing, AGRIMAX RT 955 has a high load capacity.

UM

International Standard

Construction



RADIAL

Machinery

Agriculture: Sprayer • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	300/95 R 52 (12.4 R 52)
LI/SS	151 A8/B

Dimensions International Standard

Section Width (mm)	295
Overall Diameter (mm)	1891
Static Loaded Radius (mm)	889
Rolling Circumference (mm)	5774
SRI (mm)	900
Rim Rec	W 9
Rim Alt	W 10 ; W 11 ; DW 10 ; DW 11
ECE	E4-106R-001484
TRA Code	R1

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4
50	1350	1760	2140	2350	2485	2730	2970	3210	3450	-
40	1350	1760	2140	2350	2485	2730	2970	3210	3450	-
30	1445	1885	2295	2515	2665	2920	3180	3440	3695	-
10	1605	2020	2485	2950	3420	3520	3935	4350	4765	5175

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 2:14 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..