

# AGRIMAX RT 955 - Technical Specifications



## Description

AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying and vineyards. The special tread design with a rounded shoulder provides excellent traction performance, stability and self-cleaning properties. Thanks to its strong casing, AGRIMAX RT 955 has a high load capacity.

## UM

US Standard

## Construction

 RADIAL

## Machinery

Agriculture: Sprayer • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	340/85 R 46 (13.6 R 46)
LI/SS	150 A8/B

## Dimensions US Standard

Usa code	94044726
Section Width (inch)	13.9
Overall Diameter (inch)	68.7
Static Loaded Radius (inch)	32.5
Rolling Circumference (inch)	210.5
Rim Rec	W 12
Rim Alt	W 11
ECE	E4-106R-001828
TRA Code	R1

## Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52	58
30	3190	4140	5030	5470	5840	6430	6940	7400	-
25	3190	4140	5030	5470	5840	6430	6940	7400	-
20	3410	4430	5380	5850	6250	6880	7430	7900	-
5	4550	5870	7100	7760	8310	9090	9870	10530	11080

Printed on 4/19/2024 10:53 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..