

AGRIMAX RT 955 - Technical Specifications



Description

AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying and vineyards. The special tread design with a rounded shoulder provides excellent traction performance, stability and self-cleaning properties. Thanks to its strong casing, AGRIMAX RT 955 has a high load capacity.

UM

International Standard

Construction



RADIAL

Machinery

Agriculture: Sprayer • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	340/85 R 48 (13.6 R 48)
LI/SS	151D/154A8

Dimensions International Standard

Section Width (mm)	353
Overall Diameter (mm)	1797
Static Loaded Radius (mm)	855
Rolling Circumference (mm)	5572
SRI (mm)	875
Rim Rec	W 12
Rim Alt	W 11
ECE	E11-106R-005765
TRA Code	R1

Load capacity (Kg)

km/h / bar	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4
65	1485	1660	1865	2040	2245	2385	2625	2830	3005	3175	3450
50	1560	1740	1960	2140	2360	2505	2755	2975	3155	3335	3625
40	1615	1800	2025	2215	2440	2590	2850	3075	3265	3450	370
30	1710	1910	2145	2345	2585	2740	3020	3260	3455	3655	3970
10	2230	2485	2975	3055	3365	3575	3935	4245	4505	4765	5175

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 4:50 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..