



AGRIMAX RT 955 - Data Sheet



Description

AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying and vineyards. The special tread design with a rounded shoulder provides excellent traction performance, stability and self-cleaning properties. Thanks to its strong casing, AGRIMAX RT 955 has a high load capacity.

UM

US Standard

Construction

RADIAL

Machinery

Agriculture: Sprayer • Vineyard Harvester

| SIZE | Version | USACode | TRA Code | LI/SS | RIM REC | RIM ALT | SW | OD | SLR | RC | Type | ECE |
|-----------------------------------|----------|----------|----------|------------|---------|-----------------------------|------|------|------|-------|------|-----------------|
| 210/90 R 24 (8.3 R 24) | STANDARD | 94042531 | R1 | 107 A8/B | W 7 | W 6 | 8.4 | 39.8 | 18.2 | 119.2 | TL | E4-106R-001818 |
| 210/95 R 28 (8.3 R 28) | STANDARD | 94042548 | R1 | 116 A8/B | W 7 | W 6 | 8.4 | 43.7 | 20.2 | 132.4 | TL | E4-106R-001819 |
| 210/95 R 32 (8.3 R 32) | STANDARD | 94040018 | R1 | 120 A8/B | W 7 | W 6 | 8.4 | 47.8 | 22.5 | 145.8 | TL | E4-106R-001391 |
| 230/95 R 32 (9.5 R 32) | STANDARD | 94026678 | R1 | 128 A8/B | W 7 | W 8 | 9 | 49.3 | 23 | 150 | TL | E4-106R-000764 |
| 270/95 R 32 (11.2 R 32) | STANDARD | 94021857 | R1 | 136 A8/B | W 9 | W 8 ; W 10 | 10.8 | 52.2 | 24.2 | 160.5 | TL | E4-106R-000776 |
| 230/95 R 36 (9.5 R 36) | STANDARD | 94027477 | R1 | 130 A8/B | W 8 | W 7 | 9.4 | 53.2 | 25.2 | 161.9 | TL | E4-106R-000765 |
| 270/80 R 36 | STANDARD | 94067046 | R1 | 134 A8/B | W9 | W8; W10 | 10.8 | 53 | 24.8 | 161 | TL | E11-106R-006758 |
| 270/95 R 36 (11.2 R 36) | STANDARD | 94027484 | R1 | 139 A8/B | W 9 | W 8 ; W 10 | 10.8 | 56.2 | 26.2 | 172 | TL | E4-106R-000659 |
| 270/95 R 38 (11.2 R 38) | STANDARD | 94028139 | R1 | 140 A8/B | W 9 | W 8 ; W 10 | 10.8 | 58.2 | 27.4 | 177.6 | TL | E4-106R-000657 |
| 230/95 R 40 (9.5 R 40) | STANDARD | 94055210 | R1 | 132 A8/B | W 7 | W 8 | 9 | 57.2 | 27.2 | 175 | TL | E11-106R-004066 |
| 230/95 R 42 (9.5 R 42) | STANDARD | 94028610 | R1 | 133 A8/B | W 8 | W 7 | 9.4 | 59.3 | 28.1 | 180.9 | TL | E4-106R-000772 |
| 300/85 R 42 (11.2 R 42) | STANDARD | 94040636 | R1 | 144 A8/B | W 9 | W 10 ; W 11 | 11.6 | 62.1 | 29.3 | 190.9 | TL | E4-106R-001396 |
| 210/95 R 44 (8.3 R 44) | STANDARD | 94042760 | R1 | 120 A8/B | W 7 | W 6 | 8.4 | 59.8 | 28.4 | 183.2 | TL | E4-106R-000771 |
| 230/95 R 44 (9.5 R 44) | STANDARD | 94027415 | R1 | 134 A8/B | W 8 | W 7 | 9.4 | 61.3 | 29.1 | 188.5 | TL | E4-106R-000777 |
| 270/95 R 44 (11.2 R 44) | STANDARD | 94028146 | R1 | 142 A8/B | W 9 | W 8 ; W 10 | 10.8 | 64.3 | 30.1 | 196.2 | TL | E4-106R-00784 |
| 270/95 R 46 (11.2 R 46) | STANDARD | 94042555 | R1 | 143 A8/B | W 9 | W 8 ; W 10 | 10.8 | 66.3 | 31.2 | 203.5 | TL | E4-106R-000785 |
| 300/95 R 46 (12.4 R 46) | STANDARD | 94021871 | R1 | 148 A8/B | W 9 | W 10 ; W 11 ; DW 10 ; DW 11 | 11.6 | 68.4 | 32 | 209.4 | TL | E4-106R-000790 |
| 340/85 R 46 (13.6 R 46) | STANDARD | 94044726 | R1 | 150 A8/B | W 12 | W 11 | 13.9 | 68.7 | 32.5 | 210.5 | TL | E4-106R-001828 |
| 230/95 R 48 (9.5 R 48) | STANDARD | 94021864 | R1 | 136 A8/B | W 8 | W 7 | 9.4 | 65.2 | 31.2 | 200.2 | TL | E4-106R-000778 |
| 230/95 R 48 (9.5 R 48) | STANDARD | 94052837 | R1 | 136D/139A8 | W 8 | W 7 | 9.4 | 65.2 | 31.2 | 200.2 | TL | E11-106R-004067 |
| 270/95 R 48 (11.2 R 48) | STANDARD | 94021840 | R1 | 144 A8/B | W 9 | W 8 ; W 10 | 10.8 | 68.2 | 32.3 | 210.7 | TL | E4-106R-000782 |
| 340/85 R 48 (13.6 R 48) | STANDARD | 94059287 | R1 | 151D/154A8 | W 12 | W 11 | 13.9 | 70.7 | 33.7 | 219.4 | TL | E11-106R-005765 |
| 340/85 R 48 | STANDARD | 94029426 | R1 | 152 A8/B | W 12 | W 11 | 13.9 | 70.7 | 33.7 | 219.4 | TL | E4-106R-000800 |

| | | | | | | | | | | | | |
|--|----------|----------|----|----------|-----|--------------------------|------|------|------|-------|----|----------------|
| (13.6 R 48) | | | | | | | | | | | | |
| 300/95 R 52 (12.4 R 52) | STANDARD | 94029747 | R1 | 151 A8/B | W 9 | W 10; W 11; DW 10; DW 11 | 11.6 | 74.4 | 35 | 227.3 | TL | E4-106R-001484 |
| 270/95 R 54 (11.2 R 54) | STANDARD | 94032839 | R1 | 146 A8/B | W 9 | W 8; W 10 | 10.8 | 74.2 | 35.2 | 228.9 | TL | E4-106R-001410 |

Printed on 12/9/2023 2:57 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..