

AGRIMAX SIRIO - Data Sheet



Description

AGRIMAX SIRIO is a high-speed tire (up to 70 km/h - 45 mph) developed by BKT for high-performance tractors. Its design is perfect for both haulage and soil tillage applications. The high sidewall flexibility ensures outstanding stability, handling and comfort to improve the driving experience. It is also available with IF technology that allows to carry heavy loads at a low inflating pressure. The reinforced casing and the high number of belts guarantee great traction on the field whereas the low rolling resistance contributes to better fuel economy.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: High-Power Tractor

SIZE	Version	TRA Code	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
540/65 R 30	HIGH SPEED	R1W	150 D/147 E	W 16 L	W 18	530	1464	669	4400	700	TL	E4-106R-000814
IF 600/70 R 30	HIGH SPEED	R1W	165 D/162 E	DW 21 B	DW 20 B	603	1602	713	4759	750	TL	E4-106R-000817
540/65 R 34	HIGH SPEED	R1W	152 D/149 E	W 16 L	W 18	530	1566	721	4735	750	TL	E4-106R-000815
540/65 R 38	HIGH SPEED	R1W	153 D/150 E	W 16 L	W 18 L	530	1667	769	5050	800	TL	E4-106R-000816
710/70 R 38	HIGH SPEED	R1W	171 D/168 E	DW 23 B	DW 25 B	716	1959	887	5840	925	TL	E4-106R-000818

Printed on 4/26/2024 6:48 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..