

AGRIMAX SPARGO - Technical Specifications



Description

AGRIMAX SPARGO is the special BKT tire for row crop applications. It has been designed for enhanced productivity in the fields and for preserving the soil in the long term. Thanks to VF technology, the tire provides higher load capacity at standard pressure. Thanks to a strong casing and an increased number of lugs, AGRIMAX SPARGO ensures outstanding durability along with strong stability both in the fields and during road transfers.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer

Version	STANDARD
Type	TL
Tyre Size	VF 380/90 R 46
LI/SS	173 D

Dimensions US Standard

Usa code	94038756
Section Width (inch)	15.4
Overall Diameter (inch)	72.9
Static Loaded Radius (inch)	33.3
Rolling Circumference (inch)	220.9
Rim Rec	DW 13 B
Rim Alt	W 13 A ; DW 12
ECE	E4-106R-000796
TRA Code	R1

Load capacity (lbs)

mph / psi	17	20	23	26	29	32	35	38	41	44	46	49	52	55	58	61	64
45	6250	7040	7690	8080	8470	8730	9000	9520	9910	10300	10700	11080	11350	11730	12000	12520	13040
From 40 to 25	6880	7740	8460	8890	9320	9610	9890	10470	10900	11330	11750	12180	12470	12900	13190	13760	14330
20	7020	7900	8620	9070	9500	9790	10080	10660	11100	11550	11990	12430	12710	13150	13440	14030	14620
12	7150	8050	8790	9240	9680	9980	10280	10870	11330	11780	12220	12670	12970	13410	13710	14300	14910
5	7570	8510	9300	9770	10240	10560	10870	11500	11980	12450	12920	13400	13720	14190	14500	15130	15770

Printed on 4/17/2024 9:31 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..