

# AGRIMAX SPARGO - Technical Specifications



## Description

AGRIMAX SPARGO is the special BKT tire for row crop applications. It has been designed for enhanced productivity in the fields and for preserving the soil in the long term. Thanks to VF technology, the tire provides higher load capacity at standard pressure. Thanks to a strong casing and an increased number of lugs, AGRIMAX SPARGO ensures outstanding durability along with strong stability both in the fields and during road transfers.

## UM

International Standard

## Construction

 RADIAL

## Machinery

Agriculture: Sprayer

|           |                |
|-----------|----------------|
| Version   | STANDARD       |
| Type      | TL             |
| Tyre Size | VF 380/90 R 46 |
| LI/SS     | 175 D          |

## Dimensions International Standard

|                            |                 |
|----------------------------|-----------------|
| Section Width (mm)         | 390             |
| Overall Diameter (mm)      | 1852            |
| Static Loaded Radius (mm)  | 848             |
| Rolling Circumference (mm) | 5582            |
| SRI (mm)                   | 875             |
| Rim Rec                    | DW 13 B         |
| Rim Alt                    | W 13 A ; DW 12  |
| ECE                        | E11-106R-007527 |
| TRA Code                   | R1              |

## Load capacity (Kg)

| km/h / bar    | 1.2  | 1.4  | 1.6  | 1.8  | 2.0  | 2.2  | 2.4  | 2.6  | 2.8  | 3.0  | 3.2  | 3.4  | 3.6  | 3.8  | 4.0  | 4.2  | 4.4  | 4.6  |
|---------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| 70            | 2835 | 3190 | 3485 | 3665 | 3480 | 3960 | 4080 | 4315 | 4495 | 4670 | 4850 | 5025 | 5145 | 5320 | 5440 | 5675 | 5915 | 6210 |
| From 65 to 40 | 3120 | 3510 | 3835 | 4030 | 4225 | 4355 | 4485 | 4745 | 4940 | 5135 | 5330 | 5525 | 5655 | 5850 | 5980 | 6240 | 6500 | 6900 |
| 30            | 3180 | 3580 | 3910 | 4110 | 4305 | 4440 | 4570 | 4835 | 5035 | 5235 | 5435 | 5635 | 5765 | 5965 | 6095 | 6360 | 6630 | 7040 |
| 20            | 3240 | 3650 | 3985 | 4190 | 4390 | 4525 | 4660 | 4930 | 5135 | 5340 | 5540 | 5745 | 5880 | 6080 | 6215 | 6485 | 6760 | 7180 |
| 10            | 3430 | 3860 | 4215 | 4430 | 4645 | 4790 | 4930 | 5215 | 5430 | 5645 | 5860 | 6075 | 6220 | 6435 | 6575 | 6860 | 7150 | 7590 |

Printed on 4/17/2024 9:19 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..