

# AGRIMAX SPARGO - Technical Specifications



## Description

AGRIMAX SPARGO is the special BKT tire for row crop applications. It has been designed for enhanced productivity in the fields and for preserving the soil in the long term. Thanks to VF technology, the tire provides higher load capacity at standard pressure. Thanks to a strong casing and an increased number of lugs, AGRIMAX SPARGO ensures outstanding durability along with strong stability both in the fields and during road transfers.

## UM

US Standard

## Construction

 RADIAL

## Machinery

Agriculture: Sprayer

Version	STANDARD
Type	TL
Tyre Size	VF 480/80 R 50
LI/SS	179 D

## Dimensions US Standard

Usa code	94057290
Section Width (inch)	18.9
Overall Diameter (inch)	80.2
Static Loaded Radius (inch)	37.3
Rolling Circumference (inch)	245
Rim Rec	DW 16 L
Rim Alt	DW 15 L
ECE	E11-106R-004757
TRA Code	R1

## Load capacity (lbs)

mph / psi	17	20	23	26	29	32	35	38	41	44	47	49	52
45	8700	9640	10560	11040	11660	11960	12270	12900	13520	13990	14610	15070	15550
from 40 to 25	9570	10600	11620	12130	12810	13150	13500	14180	14860	15380	16060	16570	17090
20	9760	10810	11850	12370	13070	13420	13760	14470	15160	15680	16380	16900	17430
12	9950	11020	12090	12610	13330	13680	14040	14740	15460	15990	16700	17230	17770
5	10520	11660	12780	13340	14090	14470	14840	15600	16350	16910	17660	18230	18800

Printed on 4/17/2024 8:58 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..