

AGRIMAX TERIS - Technical Specifications



Description

Today's high-power harvesters require tires that are able to support heavy equipment and loads without damaging the crops. BKT is committed to provide you with radial tires at the cutting edge to increase your yield. AGRIMAX TERIS is the right partner for all your combined operations. Excellent traction properties and high load capacity are its essential features providing best performance in all harvesting operations. The special sidewall protection and a reinforced shoulder increase resistance - thus extending the product life-cycle - also in harsh conditions and if there are stubbles in the fields.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Cotton Picker • Harvester

Version	STANDARD
Type	TL
Tyre Size	620/75 R 26 CHO
LI/SS	166 A8/B

Dimensions US Standard

Usa code	94035809
Section Width (inch)	24.6
Overall Diameter (inch)	62.6
Static Loaded Radius (inch)	28.7
Rolling Circumference (inch)	191
Rim Rec	DW 20 B
ECE	E4-106R-001419

Load capacity (lbs)

mph / psi	12	15	20	23	29	35	41	46
30	5380	6190	7590	8300	9120	9930	10760	11680
25	5380	6190	7590	8300	9120	9930	10760	11680
20	5760	6640	8130	8880	9770	10640	11520	12510
10 Cyc	8870	10220	12530	13690	15050	16390	17750	19280
5 Cyc	9680	11150	13680	14940	16410	17880	19360	21030

Printed on 4/20/2024 6:03 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..