

# AGRIMAX V-FLECTO - Technical Specifications



## Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the innovative VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.

## UM

US Standard

## Construction

 RADIAL

## Machinery

Agriculture: High-Power Tractor

Version	STANDARD
Type	TL
Tyre Size	VF 280/70 R 18
LI/SS	116 D

Dimensions US Standard

Usa code	94076468
Section Width (inch)	10.8
Overall Diameter (inch)	33.4
Static Loaded Radius (inch)	14.8
Rolling Circumference (inch)	99
Rim Rec	W 9
Rim Alt	9
ECE	E11-106R-0010341

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
45	1370	1600	1820	2050	2270	2500
from 40 to 25	1510	1760	2010	2260	2500	2760
20	1540	1800	2050	2300	2560	2810
12	1580	1830	2080	2350	2600	2870
5	1660	1940	2200	2480	2760	3030
*Upto 5 Cyc with front loader	2120	2470	2810	3160	3510	3860
10HT	1540	1800	2050	2300	2560	2810

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 10:31 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..