

AGRIMAX V-FLECTO - Technical Specifications



Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the exclusive VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: High-Power Tractor

Version	STANDARD
Type	TL
Tyre Size	VF 600/65 R 28 NRO
LI/SS	163 D

Dimensions US Standard

Usa code	94070930
Section Width (inch)	23.5
Overall Diameter (inch)	58.7
Static Loaded Radius (inch)	25.8
Rolling Circumference (inch)	175.3
Rim Rec	DW 21 B
Rim Alt	DW 20 B
Narrow Rim option	DW 18 L
ECE	E11-106R-007602
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29
45	4990	5780	6560	7440	8130	8820	9790
From 40 to 25	5490	6350	7210	8170	8930	9680	10750
20	5600	6480	7350	8340	9100	9880	10970
12	5710	6600	7500	8500	9280	10060	11180
5	6040	6990	7930	8990	9820	10650	11830
*Upto 5 Cyc with front loader	7680	8880	10090	11440	12490	13550	15050
5 HT	5600	6480	7350	8340	9100	9880	10970

* *For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Printed on 4/25/2024 11:59 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..