

AGRIMAX V-FLECTO - Technical Specifications



Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the innovative VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: High-Power Tractor

Version	STANDARD
Type	TL
Tyre Size	VF 650/60 R 38 NRO
LI/SS	166 D

Dimensions International Standard

Section Width (mm)	650
Overall Diameter (mm)	1745
Static Loaded Radius (mm)	774
Rolling Circumference (mm)	5231
SRI (mm)	825
Rim Rec	DW 23 B
Rim Alt	DW 21 B
Narrow Rim option	DW 20 B
ECE	E11-106R-005712
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
70	2650	3080	3515	3950	4385	4820
from 65 to 40	2915	3390	3865	4345	4820	5300
30	2970	3455	3940	4430	4915	5405
20	3030	3525	4015	4515	5010	5510
10	3205	3725	4250	4775	5300	5830
*Upto 10 Cyc with front loader	4080	4745	5410	6080	6745	7420
10HT	2970	3455	3940	4430	4915	5405

* *For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 6:46 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..