

AGRIMAX V-FLECTO - Technical Specifications



Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the innovative VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: High-Power Tractor

Version	STANDARD
Type	TL
Tyre Size	VF 650/75 R 38 NRO
LI/SS	175 D

Dimensions US Standard

Usa code	94512164
Section Width (inch)	26.6
Overall Diameter (inch)	76.4
Static Loaded Radius (inch)	32.8
Rolling Circumference (inch)	228.2
Rim Rec	DW 23 B
Rim Alt	DW 21 B
Narrow Rim option	DW 20 B
ECE	E11-106R-0010663
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
45	7610	8850	10100	11340	12590	13830
from 40 to 25	8370	9730	11100	12470	13830	15210
20	8520	9920	11320	12710	14110	15510
12	8700	10120	11540	12960	14380	15820
5	9190	10700	12210	13710	15220	16730
*Upto 5 Cyc with front loader	11710	13620	15540	17460	19380	21300
5 HT	8520	9920	11320	12710	14110	15510

* *For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/2/2025 1:48 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..