



AIROMAX AM 27 - Data Sheet



Description

AIROMAX AM 27 is the ideal road-oriented tire for construction applications with cranes. It features extraordinary heat resistance and outstanding riding comfort. AIROMAX AM 27 is a high-speed tire particularly suitable for all operations requiring a high level of handling.

UM

US Standard

Construction

 RADIAL

Machinery

Industrial: Mobile Crane

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	ECE
385/95 R 24 (14.00 R 24)	STANDARD	94044207	170 F	10.00W		14.6	53.7	24.6	164.4	TT	E11-54R-0015910
385/95 R 25 (14.00 R 25)	STANDARD	94044214	170 F	10.00/1.5		14.6	53.7	24.6	164.4	TL	E11-54R-0015911
445/95 R 25 (16.00 R 25)	STANDARD	94039043	174 F	11.25/2.0	11.00/1.7 CR ; 11.00/1.7CRL	17.3	58.7	27.4	180.6	TL	E4-54R-0028867
505/95 R 25 (18.00 R 25)	STANDARD	94045198	186 E	13.00/2.5		19.4	63	28.7	192.9	TL	
525/80 R 25 (20.5 R 25)	STANDARD	94058785	176 F	17.00/2.0	17.00/1.7 CR	20.9	58.3	26.8	178.5	TL	E11-54R-0016681

Printed on 2/22/2024 7:29 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..