



## ARROW - Data Sheet



### Description

ARROW is suitable for transport applications with trailers. It is a road-oriented tire that provides a better mileage and a longer service life. ARROW has a high load capacity also at high speeds. An HD version made of a special compound is also available for users that require advanced performance.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Trailer

SIZE	Version	USACode	PR	RIM REC	RIM ALT	SW	OD	Type	ECE
6.50 - 14	STANDARD	94029341	10	4.5 J		6.9	27.4	TT	E4-54R-0024093
6.50 - 14 LT	HD	94035045	10	4.5 J		6.9	27.4	TT	
7.50 - 16	STANDARD	94013197	12	6.00 G	5.50 F	8.5	32.5	TT	
7.50 - 16	STANDARD	94013203	14	6.00 G	5.50 F	8.5	32.5	TT	
7.50 - 16	STANDARD	94013210	16	6.00 G	5.50 F	8.5	32.5	TT	
10.00 - 20	STANDARD	94022472	16	7.5	7.0 ; 8.0	11.3	42.3	TT	
9.00 - 20	STANDARD	94022489	14	7.0	6.5 ; 7.5	10.6	40.9	TT	
9.00 - 20	STANDARD	94022496	16	7.0	6.5 ; 7.5	10.6	40.9	TT	
9.00 - 20	TRACTOR TRAILER	94045501	16	7.0	6.5 ; 7.5	10.6	40.9	TT	

Printed on 4/26/2024 10:44 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..