

AS 504 - Technical Specifications



Description

AS 504 is an agro-industrial tire mainly designed for soil tillage, implement and material-handling operations. This tire, which features excellent self-cleaning properties and increased grip, is suitable for field trailers and telehandlers. AS 504 is available in several versions to meet specific end-user requirements: an "HD" version with a special cut-and-chip resistance compound, while the "special" version has a reinforced casing that ensures a longer tire life.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Telehandler • Field Trailer
Industrial: Telehandler

Version	HD
Type	TT
Tyre Size	6.00 - 16
LI/SS DRIVE WHEEL	91 A8
LI/SS FREE ROLLING	103 A8

Dimensions US Standard

Usa code	94046812
Ply Rating	8
Section Width (inch)	6.5
Overall Diameter (inch)	28.9
Static Loaded Radius (inch)	13.5
Rolling Circumference (inch)	86.2
Rim Rec	4.00 E
Rim Alt	4.50 E ; 4½ K
ECE	E11-106R-005195

Load capacity (lbs)

mph / psi	58
5 FR	2700
15 FR	2295
20 FR	2160
25 FR	1930
5 DW	1895
15 DW	1610
20 DW	1520
25 DW	1355

Printed on 2/22/2024 5:33 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..