

AT 171 - Technical Specifications



Description

AT 171 has been specifically designed for mud bogger tractors. The special directional and extra-deep tread design provides excellent traction on wet and muddy surfaces.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: ATV • Mud Bogger Tractor

Version	STANDARD
Type	TT
Tyre Size	AT 35 X 10 - 18
LI/SS	90 A8/ 66 F

Dimensions International Standard

Ply Rating	8
Section Width (mm)	241
Overall Diameter (mm)	900
Static Loaded Radius (mm)	417
Rolling Circumference (mm)	2646
Rim Rec	W 8
TRA Code	R1W+

Load capacity (Kg)

km/h / bar	1.40	1.00
40 MUD BOGGING	600	-
80 MUD BOGGING	300	-
40 CASUAL TRANSPORT	-	490
80 CASUAL TRANSPORT	-	245

Printed on 5/1/2024 7:05 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..