

AT 523 - Data Sheet



Description

BKT's AT 523 is a multifunctional tire designed to provide reliable performance in agricultural, turf, and industrial applications. Its tread design ensures excellent traction and self-cleaning capabilities, which are key features for tackling a variety of surfaces: from rammed earth and turf to hard surfaces typical of industrial settings. The flatter profile and enlarged center block, combined with the R-1 and R-4 type design, provide greater stability on the road, while the rounded shoulders protect the turf, preserving its integrity even under intensive operating conditions. The strong carcass and a cut-resistant tread compound make AT 523 particularly durable. This combination of ruggedness, versatility and ease of use makes AT 523 the ideal solution for those who need a single tire that can cope with a variety of situations: from soil preparation and lawn operations to industrial use.

UM

US Standard

Construction



Machinery

Agriculture: Tractor

Industrial: Compact Loader

SIZE	Version	USACode	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Туре	ECE
26 X 12.00 - 12	STANDARD	94512522	107 A8	6	10.50 I - 55 ; I - 70 ; I - 90	10½ JA ; 8½ JA	11.8	25.6	11.8	74.7	TL	E11-106R-0010613

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 6:50 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..