



AT 603 - Data Sheet



Description

AT 603 is a bias agro-industrial tire for implement machinery and backhoe loaders. AT 603 has been engineered to ensure great durability and traction on drive wheels providing best performance on every surface as well as excellent self-cleaning properties. The AT 603 "special" version has a reinforced casing, while the "HD" version offers improved cut and chip resistance.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Backhoe Loader • Implement Machinery
Industrial: Backhoe Loader

SIZE	Version	TRA Code	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
10.5/80 - 18	HD		119 A8	131 A8	10	W 9	W 8 ; 9	274	907	422	2727	425	TL	E11-106R-004546
10.5/80 - 18	SPECIAL		119 A8	131 A8	10	W 9	W 8 ; 9	274	907	422	2727	425	TL	E11-106R-004546
10.5/80 - 18	STANDARD		119 A8	131 A8	10	W 9	W 8 ; 9	274	907	422	2727	425	TL	E4-106R-002325
12.5/80 - 18	SPECIAL		129 A8	142 A8	12	W 9	11	308	1000	448	3027	475	TL	E4-106R-004350
12.5/80 - 18	STANDARD		129 A8	142 A8	12	W 9	11	308	1000	448	3027	475	TL	
12.5/80 - 18	STANDARD		135 A8	148 A8	16	W 9	11	308	1000	448	3027	475	TL	E11-106R-004351
12.5/80 - 18	STANDARD		138 A8	150 A8	18	W 9	11	308	1000	448	3027	475	TL	E11-106R-004352
15.5 - 25	STANDARD	E2/G2/L2			12	12.00/1.3	12.00/1.3 (DC)	410	1265	577	3861		TL	

Printed on 4/19/2024 8:50 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..