

# AT 621 - Technical Specifications



## Description

AT 621 is suitable for backhoe loaders and compact loaders in all digging and loading operations in agriculture. The AT 621 tire features an extra deep tread which ensures great cut and chip resistance and higher durability. In addition, this BKT tire ensures great durability and self cleaning properties. AT 621 is available in several versions to meet the most differing user requirements.

## UM

International Standard

## Construction

 BIAS

## Machinery

Agriculture: Compact Loader • Backhoe Loader  
 Industrial: Backhoe Loader • Loader

Version	SPECIAL
Type	TL
Tyre Size	12.5/80 - 18
LI/SS DRIVE WHEEL	129 A8
LI/SS FREE ROLLING	142 A8

## Dimensions International Standard

Ply Rating	12
Section Width (mm)	308
Overall Diameter (mm)	987
Static Loaded Radius (mm)	434
Rolling Circumference (mm)	2916
Rim Rec	W 9
Rim Alt	11.0
ECE	E11-106R-005329
TRA Code	R4

## Load capacity (Kg)

	km/h / bar	3.70
	10 FR	3710
	25 FR	3155
	30 FR	2970
	40 FR	2650
	10 DW	2590
	25 DW	2200
	30 DW	2070
	40 DW	1850

Printed on 4/19/2024 7:19 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..