

AW 09 - Technical Specifications



Description

AW 09 has been developed for soil tillage, hay harvesting and transport applications with implements, balers and trailers. It is ideal for modern farming both on and off the road. Its reinforced carcass ensures high load capacity and a longer service tire life. AW 09 has been designed with a special cut-and-chip-resistant compound that provides extraordinary stubble resistance.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Baler • Hay Harvester • Implement Machinery
• Trailer

Version	STANDARD
Type	TL
Tyre Size	380/55 - 17
LI/SS DRIVE WHEEL	128 A8
LI/SS FREE ROLLING	141 A8

Dimensions International Standard

Section Width (mm)	390
Overall Diameter (mm)	850
Static Loaded Radius (mm)	377
Rolling Circumference (mm)	2491
Rim Rec	13.00
ECE	E4-106R-000380

Load capacity (Kg)

	km/h / bar	3.20
	10 FR	3605
	25 FR	3065
	30 FR	2885
	40 FR	2575
	10 DW	2520
	25 DW	2140
	30 DW	2015
	40 DW	1800

Printed on 4/23/2024 9:15 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..