

AW 702 - Technical Specifications



Description

AW 702 has been developed for implement machinery, trailers and balers in soil tillage and haulage applications. This heavy-duty tire has been designed by BKT to provide a new level of durability. AW 702 is available in different versions to meet specific end-user needs: an "aramid belted" version is available for those who need strengthened puncture resistance, the "HD" version has a special cut-and-chip resistant compound, while the "special" version provides extraordinary stubble resistance.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Baler • Implement Machinery • Trailer
Industrial: Trailer

| | |
|--------------------|--------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 13.0/55 - 16 |
| LI/SS FREE ROLLING | 130 A8 |

Dimensions US Standard

| | |
|------------------------------|----------------|
| Usa code | 94009718 |
| Ply Rating | 12 |
| Section Width (inch) | 13.2 |
| Overall Diameter (inch) | 30.3 |
| Static Loaded Radius (inch) | 13.6 |
| Rolling Circumference (inch) | 88.8 |
| Rim Rec | 11.0 |
| ECE | E4-106R-001898 |

Load capacity (lbs)

| | |
|-----------|------|
| mph / psi | 77 |
| 5 FR | 5860 |
| 15 FR | 4980 |
| 20 FR | 4700 |
| 25 FR | 4190 |

Printed on 5/3/2024 7:17 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..