



AW 702 - Data Sheet



Description

AW 702 has been developed for implement machinery, trailers and balers in soil tillage and haulage applications. This heavy-duty tire has been designed by BKT to provide a new level of durability. AW 702 is available in different versions to meet specific end-user needs: an "aramid belted" version is available for those who need strengthened puncture resistance, the "HD" version has a special cut-and-chip resistant compound, while the "special" version provides extraordinary stubble resistance.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Baler • Implement Machinery • Trailer
Industrial: Trailer

SIZE	Version	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
10.0/80 - 12	ARAMID BELTED	121 A8	10	9.00	7.0	264	710	317	2144		TL	E11-106R-003576
10.0/80 - 12	SPECIAL	121 A8	10	9.00	7.0	264	710	317	2144		TL	E11-106R-004353
10.0/80 - 12	STANDARD	121 A8	10	9.00	7.0	264	710	317	2144		TL	E4-106R-002662
10.0/80 - 12	STANDARD	116 A8	8	9.00	7.0	264	710	317	2144		TL	
7.00 - 12	ARAMID BELTED	95 A8	6	4.25		185	665	295	1948		TL	E11-106R-004243
7.00 - 12	STANDARD	95 A8	6	4.25		185	665	295	1948		TL	E4-106R-001957
10.0/75 - 15.3	HD	135 A8	18	9.00		274	760	351	2213		TL	E11-106R-005317
10.0/75 - 15.3	SPECIAL	130 A8	14	9.00		274	760	351	2213		TL	E4-106R-001542
10.0/75 - 15.3	STANDARD	126 A8	12	9.00		274	760	351	2213		TT	E4-106R-001541
10.0/75 - 15.3	STANDARD	126 A8	12	9.00		274	760	351	2213		TL	E4-106R-001541
10.0/75 - 15.3	STANDARD	130 A8	14	9.00		274	760	351	2213		TT	E4-106R-001896
10.0/75 - 15.3	STANDARD	130 A8	14	9.00		274	760	351	2213		TL	E4-106R-001896
10.0/75 - 15.3	STANDARD	135 A8	18	9.00		274	760	351	2213		TL	E4-106R-001880
10.0/75 - 15.3	STANDARD	137 A8	22	9.00		274	760	351	2213		TL	E4-106R-002260
10.0/75 - 15.3	STANDARD	119 A8	8	9.00		274	760	351	2213		TT	
10.0/75 - 15.3	STANDARD	123 A8	10	9.00		274	760	351	2213		TT	E4-106R-001540
10.0/75 - 15.3	STANDARD	123 A8	10	9.00		274	760	351	2213		TL	E4-106R-001540
11.5/80 - 15.3	ARAMID BELTED	139 A8	14	9.00		297	844	370	2473		TL	E11-106R-004548
11.5/80 - 15.3	STANDARD	131 A8	10	9.00		297	844	370	2473		TL	E4-106R-001893
11.5/80 - 15.3	STANDARD	135 A8	12	9.00		297	844	370	2473		TT	E4-106R-001895
11.5/80 - 15.3	STANDARD	135 A8	12	9.00		297	844	370	2473		TL	E4-106R-001895
11.5/80 - 15.3	STANDARD	139 A8	14	9.00		297	844	370	2473		TT	E4-106R-001897
11.5/80 - 15.3	STANDARD	139 A8	14	9.00		297	844	370	2473		TL	E4-106R-001897
11.5/80 - 15.3	STANDARD	141 A8	16	9.00		297	844	370	2473		TT	E4-106R-002752
11.5/80 - 15.3	STANDARD	143 A8	18	9.00		297	844	370	2473		TT	E4-106R-001881
11.5/80 - 15.3	STANDARD	131 A8	10	9.00		297	844	370	2473		TT	E4-106R-001893
11.5/80 - 15.3	STANDARD	143 A8	18	9.00		297	844	370	2473		TL	E4-106R-001881
11.5/80 - 15.3	STANDARD	141 A8	16	9.00		297	844	370	2473		TL	E4-106R-002752
12.5/80 - 15.3	SPECIAL	142 A8	14	9.00		312	885	387	2593		TT	E11-106R-004354
12.5/80 - 15.3	SPECIAL	146 A8	18	9.00		312	885	387	2593		TL	E11-106R-004356
12.5/80 - 15.3	STANDARD	144 A8	16	9.00		312	885	387	2593		TL	E11-106R-004355
12.5/80 - 15.3	STANDARD	142 A8	14	9.00		312	885	387	2593		TL	E11-106R-003602
12.5/80 - 15.3	STANDARD	144 A8	16	9.00		312	885	387	2593		TT	E11-106R-004355
12.5/80 - 15.3	STANDARD	142 A8	14	9.00		312	885	387	2593		TT	E11-106R-003602
10.5/65 - 16	INDUSTRIAL	130 A8	14	W 9	W 8 ; W 8 L	270	760	343	2112		TL	E11-106R-004247
10.5/65 - 16	SPECIAL	123 A8	10	W 9	W 8 ; W 8 L	270	760	350	2329		TL	E11-106R-004245
10.5/65 - 16	STANDARD	123 A8	10	W 9	W 8 ; W 8 L	270	760	350	2329		TT	E11-106R-003513
10.5/65 - 16	STANDARD	123 A8	10	W 9	W 8 ; W 8 L	270	760	350	2329		TL	E11-106R-003513
10.5/65 - 16	STANDARD	130 A8	14	W 9	W 8 ; W 8 L	270	760	350	2329		TT	E11-106R-003351
10.5/65 - 16	STANDARD	130 A8	14	W 9	W 8 ; W 8 L	270	760	350	2329		TL	E11-106R-003351
10.50 - 16	STANDARD		14	6.00 T		305	975	445	2986		TT	E11-106R-004244
13.0/55 - 16	STANDARD	130 A8	12	11.0		336	770	345	2256		TL	E4-106R-001898
13.0/55 - 16	STANDARD	133 A8	14	11.0		336	770	345	2256		TL	E4-106R-002751
13.0/55 - 16	STANDARD	138 A8	18	11.0		336	770	345	2256		TL	E4-106R-002332

13.0/75 - 16	STANDARD	135 A8	10	11.0	9 ; W 9 ; W 11	340	890	396	2726	TL	E4-106R-001899	
6.00 - 16	STANDARD	95 A8	6	4.00 E	4.50 E ; 4½ K	169	722	334	2197	TL	E4-106R-001958	
6.00 - 16	STANDARD	103 A8	8	4.00 E	4.50 E ; 4½ K	169	722	334	2197	TT	E11-106R-004357	
6.00 - 16	STANDARD	95 A8	6	4.00 E	4.50 E ; 4½ K	169	722	334	2197	TT	E4-106R-001958	
10.5/80 - 18	STANDARD	131 A8	10	W 9	W 8 ; 9	275	885	395	2593	TL	E4-106R-002326	
10.5/80 - 18	STANDARD	138 A8	14	W 9	W 8 ; 9	275	885	395	2593	TL	E11-106R-003577	
12.5/80 - 18	SPECIAL	145 A8	14	W 9	11	308	965	432	2827	TL		
12.5/80 - 18	SPECIAL	148 A8	16	W 9	11	308	965	432	2827	TL	E11-106R-004359	
12.5/80 - 18	STANDARD	148 A8	16	W 9	11	308	965	432	2827	TL	E4-106R-001907	
12.5/80 - 18	STANDARD	150 A8	18	W 9	11	308	965	432	2827	TL		
12.5/80 - 18	STANDARD	142 A8	12	W 9	11	308	965	432	2827	TL		
12.5/80 - 18	STANDARD	145 A8	14	W 9	11	308	965	432	2827	TL	E4-106R-001906	
12.5/80 - 18	STANDARD	139 A8	10	W 9	11	308	965	432	2827	TL		
13.0/65 - 18	STANDARD	144 A8	16	11.0		336	890	398	2608	425	TL	E4-106R-001905
13.0/65 - 18	STANDARD	141 A8	14	11.0		336	890	398	2608	425	TT	E11-106R-004248
13.0/65 - 18	STANDARD	141 A8	14	11.0		336	890	398	2608	425	TL	
14.5/80 - 18	STANDARD	155 A8	12	11.0	12 ; 13	374	1047	446	3068	TT	E11-106R-003601	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/27/2025 1:36 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..