



## AW 702 - Data Sheet



### Description

AW 702 has been developed for implement machinery, trailers and balers in soil tillage and haulage applications. This heavy-duty tire has been designed by BKT to provide a new level of durability. AW 702 is available in different versions to meet specific end-user needs: an "aramid belted" version is available for those who need strengthened puncture resistance, the "HD" version has a special cut-and-chip resistant compound, while the "special" version provides extraordinary stubble resistance.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Baler • Implement Machinery • Trailer  
Industrial: Trailer

SIZE	Version	USACode	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
10.0/80 - 12	ARAMID BELTED	94039777	121 A8	10	9.00	7.0	10.4	28	12.5	84.4	TL	E11-106R-003576
10.0/80 - 12	SPECIAL	94040001	121 A8	10	9.00	7.0	10.4	28	12.5	84.4	TL	E11-106R-004353
10.0/80 - 12	STANDARD	94009176	121 A8	10	9.00	7.0	10.4	28	12.5	84.4	TL	E4-106R-002662
10.0/80 - 12	STANDARD	94009152	116 A8	8	9.00	7.0	10.4	28	12.5	84.4	TL	
7.00 - 12	ARAMID BELTED	94048007	95 A8	6	4.25		7.3	26.2	11.6	76.7	TL	E11-106R-004243
7.00 - 12	STANDARD	94019755	95 A8	6	4.25		7.3	26.2	11.6	76.7	TL	E4-106R-001957
10.0/75 - 15.3	HD	94048472	135 A8	18	9.00		10.8	29.9	13.8	87.1	TL	E11-106R-005317
10.0/75 - 15.3	SPECIAL	94048342	130 A8	14	9.00		10.8	29.9	13.8	87.1	TL	E4-106R-001542
10.0/75 - 15.3	STANDARD	94009060	126 A8	12	9.00		10.8	29.9	13.8	87.1	TT	E4-106R-001541
10.0/75 - 15.3	STANDARD	94009077	126 A8	12	9.00		10.8	29.9	13.8	87.1	TL	E4-106R-001541
10.0/75 - 15.3	STANDARD	94009107	130 A8	14	9.00		10.8	29.9	13.8	87.1	TT	E4-106R-001896
10.0/75 - 15.3	STANDARD	94009114	130 A8	14	9.00		10.8	29.9	13.8	87.1	TL	E4-106R-001896
10.0/75 - 15.3	STANDARD	94009138	135 A8	18	9.00		10.8	29.9	13.8	87.1	TL	E4-106R-001880
10.0/75 - 15.3	STANDARD	94044320	137 A8	22	9.00		10.8	29.9	13.8	87.1	TL	E4-106R-002260
10.0/75 - 15.3	STANDARD	94008995	119 A8	8	9.00		10.8	29.9	13.8	87.1	TT	
10.0/75 - 15.3	STANDARD	94009015	123 A8	10	9.00		10.8	29.9	13.8	87.1	TT	E4-106R-001540
10.0/75 - 15.3	STANDARD	94009022	123 A8	10	9.00		10.8	29.9	13.8	87.1	TL	E4-106R-001540
11.5/80 - 15.3	ARAMID BELTED	94041725	139 A8	14	9.00		11.7	33.2	14.6	97.4	TL	E11-106R-004548
11.5/80 - 15.3	STANDARD	94009367	131 A8	10	9.00		11.7	33.2	14.6	97.4	TL	E4-106R-001893
11.5/80 - 15.3	STANDARD	94009404	135 A8	12	9.00		11.7	33.2	14.6	97.4	TT	E4-106R-001895
11.5/80 - 15.3	STANDARD	94009411	135 A8	12	9.00		11.7	33.2	14.6	97.4	TL	E4-106R-001895
11.5/80 - 15.3	STANDARD	94009459	139 A8	14	9.00		11.7	33.2	14.6	97.4	TT	E4-106R-001897
11.5/80 - 15.3	STANDARD	94009466	139 A8	14	9.00		11.7	33.2	14.6	97.4	TL	E4-106R-001897
11.5/80 - 15.3	STANDARD	94009497	141 A8	16	9.00		11.7	33.2	14.6	97.4	TT	E4-106R-002752
11.5/80 - 15.3	STANDARD	94009503	143 A8	18	9.00		11.7	33.2	14.6	97.4	TT	E4-106R-001881
11.5/80 - 15.3	STANDARD	94009350	131 A8	10	9.00		11.7	33.2	14.6	97.4	TT	E4-106R-001893
11.5/80 - 15.3	STANDARD	94009510	143 A8	18	9.00		11.7	33.2	14.6	97.4	TL	E4-106R-001881
11.5/80 - 15.3	STANDARD	94053223	141 A8	16	9.00		11.7	33.2	14.6	97.4	TL	E4-106R-002752
12.5/80 - 15.3	SPECIAL	94051748	142 A8	14	9.00		12.3	34.8	15.2	102.1	TT	E11-106R-004354
12.5/80 - 15.3	SPECIAL	94048489	146 A8	18	9.00		12.3	34.8	15.2	102.1	TL	E11-106R-004356
12.5/80 - 15.3	STANDARD	94045273	144 A8	16	9.00		12.3	34.8	15.2	102.1	TL	E11-106R-004355
12.5/80 - 15.3	STANDARD	94009558	142 A8	14	9.00		12.3	34.8	15.2	102.1	TL	E11-106R-003602
12.5/80 - 15.3	STANDARD	94009589	144 A8	16	9.00		12.3	34.8	15.2	102.1	TT	E11-106R-004355
12.5/80 - 15.3	STANDARD	94009541	142 A8	14	9.00		12.3	34.8	15.2	102.1	TT	E11-106R-003602
10.5/65 - 16	INDUSTRIAL	94028597	130 A8	14	W 9	W 8 ; W 8 L	10.6	29.9	13.5	83.1	TL	E11-106R-004247
10.5/65 - 16	SPECIAL	94031009	123 A8	10	W 9	W 8 ; W 8 L	10.6	29.9	13.8	91.7	TL	E11-106R-004245
10.5/65 - 16	STANDARD	94009220	123 A8	10	W 9	W 8 ; W 8 L	10.6	29.9	13.8	91.7	TT	E11-106R-003513
10.5/65 - 16	STANDARD	94009237	123 A8	10	W 9	W 8 ; W 8 L	10.6	29.9	13.8	91.7	TL	E11-106R-003513
10.5/65 - 16	STANDARD	94009275	130 A8	14	W 9	W 8 ; W 8 L	10.6	29.9	13.8	91.7	TT	E11-106R-003351
10.5/65 - 16	STANDARD	94009282	130 A8	14	W 9	W 8 ; W 8 L	10.6	29.9	13.8	91.7	TL	E11-106R-003351
10.50 - 16	STANDARD	94009893		14	6.00 T		12	38.4	17.5	117.6	TT	E11-106R-004244
13.0/55 - 16	STANDARD	94009718	130 A8	12	11.0		13.2	30.3	13.6	88.8	TL	E4-106R-001898
13.0/55 - 16	STANDARD	94009725	133 A8	14	11.0		13.2	30.3	13.6	88.8	TL	E4-106R-002751
13.0/55 - 16	STANDARD	94009732	138 A8	18	11.0		13.2	30.3	13.6	88.8	TL	E4-106R-002332

<b>13.0/75 - 16</b>	STANDARD	94025640	135 A8	10	11.0	9 ; W 9 ; W 11	13.4	35	15.6	107.3	TL	E4-106R-001899
<b>6.00 - 16</b>	STANDARD	94009879	95 A8	6	4.00 E	4.50 E ; 4½ K	6.7	28.4	13.1	86.5	TL	E4-106R-001958
<b>6.00 - 16</b>	STANDARD	94026296	103 A8	8	4.00 E	4.50 E ; 4½ K	6.7	28.4	13.1	86.5	TT	E11-106R-004357
<b>6.00 - 16</b>	STANDARD	94009862	95 A8	6	4.00 E	4.50 E ; 4½ K	6.7	28.4	13.1	86.5	TT	E4-106R-001958
<b>10.5/80 - 18</b>	STANDARD	94009329	131 A8	10	W 9	W 8 ; 9	10.8	34.8	15.6	102.1	TL	E4-106R-002326
<b>10.5/80 - 18</b>	STANDARD	94009343	138 A8	14	W 9	W 8 ; 9	10.8	34.8	15.6	102.1	TL	E11-106R-003577
<b>12.5/80 - 18</b>	SPECIAL	94030989	145 A8	14	W 9	11	12.1	38	17	111.3	TL	
<b>12.5/80 - 18</b>	SPECIAL	94030606	148 A8	16	W 9	11	12.1	38	17	111.3	TL	E11-106R-004359
<b>12.5/80 - 18</b>	STANDARD	94009701	148 A8	16	W 9	11	12.1	38	17	111.3	TL	E4-106R-001907
<b>12.5/80 - 18</b>	STANDARD	94041503	150 A8	18	W 9	11	12.1	38	17	111.3	TL	
<b>12.5/80 - 18</b>	STANDARD	94009633	142 A8	12	W 9	11	12.1	38	17	111.3	TL	
<b>12.5/80 - 18</b>	STANDARD	94009671	145 A8	14	W 9	11	12.1	38	17	111.3	TL	E4-106R-001906
<b>12.5/80 - 18</b>	STANDARD	94009602	139 A8	10	W 9	11	12.1	38	17	111.3	TL	
<b>13.0/65 - 18</b>	STANDARD	94009800	144 A8	16	11.0		13.2	35	15.7	102.7	TL	E4-106R-001905
<b>13.0/65 - 18</b>	STANDARD	94009749	141 A8	14	11.0		13.2	35	15.7	102.7	TT	E11-106R-004248
<b>13.0/65 - 18</b>	STANDARD	94009756	141 A8	14	11.0		13.2	35	15.7	102.7	TL	
<b>14.5/80 - 18</b>	STANDARD	94034666	155 A8	12	11.0	12 ; 13	14.7	41.2	17.6	120.8	TT	E11-106R-003601

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/27/2025 1:43 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..