



AW 705 - Data Sheet

Description

AW 705 has been developed for implement machinery, trailers and balers in soil tillage and haulage applications. It is ideal for modern farming thanks to improved durability and high load capacity.



UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Baler • Implement Machinery • Trailer

| SIZE | Version | USACode | LI/SS FREE ROLLING | PR | RIM REC | RIM ALT | SW | OD | SLR | RC | Type | ECE |
|---------------|-------------------|----------|--------------------|----|----------|----------------------|------|------|------|-------|------|-----------------|
| 14.0/65 - 16 | STANDARD | 94009923 | 142 A8 | 14 | 11.0 | | 13.9 | 34.3 | 15.3 | 100.4 | TT | E4-106R-001901 |
| 14.0/65 - 16 | STANDARD | 94009909 | 134 A8 | 10 | 11.0 | | 13.9 | 34.3 | 15.3 | 100.4 | TT | |
| 14.0/65 - 16 | STANDARD | 94009916 | 134 A8 | 10 | 11.0 | | 13.9 | 34.3 | 15.3 | 100.4 | TL | |
| 14.0/65 - 16 | STANDARD | 94009930 | 142 A8 | 14 | 11.0 | | 13.9 | 34.3 | 15.3 | 100.4 | TL | E4-106R-001901 |
| 15.0/55 - 17 | SPECIAL | 94048335 | 134 A8 | 10 | 13.00 | 13 ; W 13 | 15 | 33.5 | 15.4 | 101.4 | TL | E11-106R-004250 |
| 15.0/55 - 17 | STANDARD | 94054022 | 155 A8 | 26 | 13.00 | 13 ; W 13 | 15 | 33.5 | 15.4 | 101.4 | TL | E11-106R-004251 |
| 15.0/55 - 17 | STANDARD | 94009978 | 134 A8 | 10 | 13.00 | 13 ; W 13 | 15 | 33.5 | 15.4 | 101.4 | TL | E4-106R-001546 |
| 15.0/55 - 17 | STANDARD | 94010028 | 138 A8 | 12 | 13.00 | 13 ; W 13 | 15 | 33.5 | 15.4 | 101.4 | TL | E4-106R-001549 |
| 15.0/55 - 17 | STANDARD | 94010066 | 141 A8 | 14 | 13.00 | 13 ; W 13 | 15 | 33.5 | 15.4 | 101.4 | TL | E4-106R-001547 |
| 15.0/55 - 17 | STANDARD | 94010097 | 146 A8 | 18 | 13.00 | 13 ; W 13 | 15 | 33.5 | 15.4 | 101.4 | TL | E4-106R-001882 |
| 15.0/70 - 18 | STANDARD | 94010110 | 145 A8 | 12 | 13.00 | 13 ; W 13 | 15.9 | 39.8 | 17.6 | 121.7 | TL | E4-106R-001902 |
| 15.0/70 - 18 | STANDARD | 94010158 | 148 A8 | 14 | 13.00 | 13 ; W 13 | 15.9 | 39.8 | 17.6 | 121.7 | TL | E4-106R-001903 |
| 15.0/70 - 18 | STANDARD | 94025749 | 151 A8 | 16 | 13.00 | 13 ; W 13 | 15.9 | 39.8 | 17.6 | 121.7 | TL | E4-106R-002266 |
| 16.0/70 - 20 | SPECIAL | 94029884 | 154 A8 | 14 | 13.0 | 12 SDC ; 13 SDC ; 14 | 16.1 | 42.3 | 18.9 | 124.2 | TL | E11-106R-004252 |
| 16.0/70 - 20 | STANDARD | 94010189 | 151 A8 | 12 | 13.0 | 12 SDC ; 13 SDC ; 14 | 16.1 | 42.3 | 18.9 | 124.2 | TT | E4-106R-002711 |
| 16.0/70 - 20 | STANDARD | 94027408 | 151 A8 | 12 | 13.0 | 12 SDC ; 13 SDC ; 14 | 16.1 | 42.3 | 18.9 | 124.2 | TL | E4-106R-002711 |
| 16.0/70 - 20 | STANDARD | 94010202 | 154 A8 | 14 | 13.0 | 12 SDC ; 13 SDC ; 14 | 16.1 | 42.3 | 18.9 | 124.2 | TT | E11-106R-003368 |
| 16.0/70 - 20 | STANDARD | 94026227 | 154 A8 | 14 | 13.0 | 12 SDC ; 13 SDC ; 14 | 16.1 | 42.3 | 18.9 | 124.2 | TL | E11-106R-003368 |
| 16.0/70 - 20 | STANDARD | 94010219 | 156 A8 | 16 | 13.0 | 12 SDC ; 13 SDC ; 14 | 16.1 | 42.3 | 18.9 | 124.2 | TL | E4-106R-002267 |
| 400/55 - 22.5 | STANDARD | 94042449 | 154 A8 | 18 | AG 11.75 | 12.25 ; AG 13.00 | 15.9 | 40 | 17.4 | 120.9 | TL | E11-106R-004550 |
| 400/55 - 22.5 | STUBBLE RESISTANT | 94060306 | 156 A8 | 20 | AG 11.75 | 12.25 ; AG 13.00 | 15.9 | 40 | 17.4 | 120.9 | TL | |

Printed on 4/26/2024 4:23 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..