# AW 726 - Technical Specifications

## Description

AW 726 has been specially designed for trailers in transport operations. It is best suited for both on-and-off-the-road usage. AW 726 shows excellent road performance and self-cleaning features. The block pattern design provides an extended tire life-cycle.

## UM

US Standard

## Construction

BIAS

## Machinery

Agriculture: Trailer

| | |
|---|---|
| **Version** | STEEL BELTED |
| **Type** | TL |
| **Tyre Size** | 11.5/80 - 15.3 |
| **LI/SS DRIVE WHEEL** | 126 A8 |
| **LI/SS FREE ROLLING** | 139 A8 |

## Dimensions US Standard

| | |
|---|---|
| **Usa code** | 94067695 |
| **Ply Rating** | 14 |
| **Section Width (inch)** | 11.8 |
| **Overall Diameter (inch)** | 33.7 |
| **Static Loaded Radius (inch)** | 14.7 |
| **Rolling Circumference (inch)** | 100 |
| **Rim Rec** | 9.00 |
| **ECE** | E11-106R-006974 |

## Load capacity (lbs)

| mph / psi | 70 |
|---|---|
| **5 FR** | 7500 |
| **15 FR** | 6370 |
| **20 FR** | 6000 |
| **25 FR** | 5360 |
| **5 DW** | 5250 |
| **15 DW** | 4460 |
| **20 DW** | 4200 |
| **25 DW** | 3750 |

Printed on 4/26/2024 9:48 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..