

AW 726 - Technical Specifications



Description

AW 726 has been specially designed for trailers in transport operations. It is best suited for both on-and-off-the-road usage. AW 726 shows excellent road performance and self-cleaning features. The block pattern design provides an extended tire life-cycle.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Trailer

Version	STANDARD
Type	TL
Tyre Size	420/55 - 17
LI/SS DRIVE WHEEL	121 A8
LI/SS FREE ROLLING	133 A8

Dimensions International Standard

Section Width (mm)	415
Overall Diameter (mm)	890
Static Loaded Radius (mm)	392
Rolling Circumference (mm)	2584
Rim Rec	13.00
ECE	E11-106R-005265

Load capacity (Kg)

km/h / bar	2.00
10 FR	2885
25 FR	2450
30 FR	2305
40 FR	2060
10 DW	2030
25 DW	1725
30 DW	1625
40 DW	1450

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/13/2025 2:20 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..