

AW 729 - Technical Specifications



Description

AW 729 is an agricultural tire specifically designed for transport, hay harvesting, baling and soil tillage applications. Its rounded shoulder and three central grooves tread design provide low soil compaction and avoids damages to the field.

AW 729 is the ideal tire for modern farming, and it is suited for both on-and-off-the-road usage.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Baler • Implement Machinery • Trailer

Version	STANDARD
Type	TL
Tyre Size	480/45 - 17
LI/SS DRIVE WHEEL	134 A8
LI/SS FREE ROLLING	146 A8

Dimensions International Standard

Section Width (mm)	480
Overall Diameter (mm)	866
Static Loaded Radius (mm)	400
Rolling Circumference (mm)	2526
Rim Rec	16.00
ECE	E11-106R-006798

Load capacity (Kg)

	km/h / bar	3.20
	10 FR	4200
	25 FR	3570
	30 FR	3360
	40 FR	3000
	10 DW	2970
	25 DW	2525
	30 DW	2375
	40 DW	2120

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 2/9/2025 4:16 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..