

## BK 826 - Technical Specifications



### Description

BK 826 has been specially designed for trailers in haulage applications. It is a bias tire featuring high load capacity thanks to its reinforced carcass. BK 826 is also available as "industrial" version that shows particular cut and chip resistance and is also suitable for backhoe loaders.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Trailer

Industrial: Backhoe Loader • Trailer

|           |                 |
|-----------|-----------------|
| Version   | TRACTOR TRAILER |
| Type      | TT              |
| Tyre Size | 9.00 - 16       |
| LI/SS     | 138 A6          |

## Dimensions US Standard

|                         |                 |
|-------------------------|-----------------|
| Usa code                | 94047017        |
| Ply Rating              | 18              |
| Section Width (inch)    | 10.4            |
| Overall Diameter (inch) | 36.4            |
| Rim Rec                 | 6.50 H          |
| Rim Alt                 | 6.00 G          |
| ECE                     | E11-106R-005356 |

## Load capacity (lbs)

|           |      |
|-----------|------|
| mph / psi | 110  |
| 20        | 5200 |

Printed on 4/27/2024 11:51 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..