

CON TRAILER - Technical Specifications



Description

CON TRAILER is a trailer tire particularly suitable for port applications. It is the ideal tire for on-and-off-the-road applications. Its robust construction results in high load capacity, whereas its extra-deep tread allows for a better mileage.

UM

US Standard

Construction



Machinery

Industrial: Trailer

| Version | PORT INDUSTRIAL |
|-----------|-----------------|
| Туре | тт |
| Tyre Size | 10.00 - 20 |

Dimensions US Standard

| Usa code | 94050369 |
|-------------------------|----------|
| Ply Rating | 18 |
| Section Width (inch) | 11.3 |
| Overall Diameter (inch) | 42.5 |
| Rim Rec | 7.5 |
| Rim Alt | 7.0; 8.0 |

Load capacity (lbs)

| mph / psi | - | - |
|-----------|---|---|
| · | - | - |
| | _ | _ |

Printed on 4/11/2024 3:50 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..