

EARTHMAX SR 22 AS - Data Sheet



Description

EARTHMAX SR 22 AS (E-2**/G-2*/L-2**) is an All Steel radial tire specially designed for graders, small loaders and trucks operating on ice and snow ensuring also optimum performance in all-season conditions.

The extraordinary tread design features deep sipes and a four-block pattern. Made of unique winter compounds, it provides superior braking performance in icy or snowy conditions and avoids stone trapping during all-season usage.

The low void ratio and wide footprint of EARTHMAX SR 22 AS stand for excellent traction and stability with even wear, and a long tread life.

UM

International Standard

Construction



RADIAL

Machinery

OTR: Grader • Loader

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
14.00 R 24	CUT RESISTANT COMPOUND	G2/L2	*	153 A8/175 A2	8.00 TG	9.00 GR , 10.00 VA	390	1370	625	4141	TL
17.5 R 25	CUT RESISTANT COMPOUND	E2/G2/L2	**/**/**	167 B/153 A8/182 A2	14.00/1.5		445	1350	595	4010	TL
20.5 R 25	CUT RESISTANT COMPOUND	E2/G2/L2	**/**/**	177 B/161 A8/193 A2	17.00/2.0		532	1493	641	4324	TL
23.5 R 25	CUT RESISTANT COMPOUND	E2/G2/L2	**/**/**	185 B/170 A8 /201 A2	19.50/2.5		610	1614	709	4863	TL

Printed on 5/3/2024 7:13 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..