

# EARTHMAX SR 22 - Technical Specifications



## Description

EARTHMAX SR 22 (G-2/L-2) is an **All Steel** radial tire specially designed for motor graders and loaders operating in extreme winter conditions on ice or snow. Operators will appreciate both excellent traction and stability provided by the large and non-directional tread design.

## UM

International Standard

## Construction

 RADIAL

## Machinery

Industrial: Dozer • Grader • Loader

OTR: Dozer • Grader • Loader

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	20.5 R 25
LI/SS	177 B/193 A2

## Dimensions International Standard

Overall Width (mm)	525
Overall Diameter (mm)	1490
Static Loaded Radius (mm)	640
Rolling Circumference (mm)	4315
Rim Rec	17.00/2.0
Rim Alt	17.00/1.7
Star Rating	**
TRA Code	E2/L2

## Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25	6.50
50	5800	6150	6500	6700	6900	7300	-	-	-	-	-
10	-	-	-	-	-	9750	10000	10300	10900	11200	11500

Printed on 12/2/2023 3:41 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..