



EARTHMAX SR 23 - Data Sheet



Description

EARTHMAX SR 23 (G-2/L-2) is an All Steel radial tire specially designed for motor graders and loaders. It features superior forward and lateral traction as well as exceptional self-cleaning properties. The durable casing and the particularly cut-resistant tread provide a long service life.

UM

US Standard

Construction



RADIAL

Machinery

OTR: Grader • Loader

| SIZE | Version | USACode | TRA Code | Star R | LI/SS | RIM REC | RIM ALT | OW | OD | SLR | RC | Type | Tread Depth |
|-----------|------------------------|----------|----------|--------|---------------|-----------|---------|------|------|------|-------|------|-------------|
| 15.5 R 25 | CUT RESISTANT COMPOUND | 94046829 | G2/L2 | * | 146 A8/169 A2 | 12.00/1.3 | | 15.1 | 49.8 | 22 | 147.9 | TL | 34 |
| 17.5 R 25 | CUT RESISTANT COMPOUND | 94060313 | G2/L2 | * | 153 A8/176 A2 | 14.00/1.5 | | 17.6 | 53 | 24.1 | 161.7 | TL | 34 |
| 20.5 R 25 | CUT RESISTANT COMPOUND | 94060603 | G2/L2 | * | 161 A8/186 A2 | 17.00/2.0 | | 21.1 | 58.7 | 26.3 | 176.7 | TL | 39 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/3/2025 10:44 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..