

EARTHMAX SR 30 - Technical Specifications



Description

EARTHMAX SR 30 (E-3/L-3) is an **All Steel** radial tire which is dual-purposed for loaders and articulated dump trucks. The multi-layer steel belts and the rigid block pattern provide excellent traction, stability and durability. The special cut-resistant compound makes EARTHMAX SR 30 the ideal solution for a variety of harsh operating conditions.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Articulated Dump Truck (ADT) • Dozer • Loader

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	26.5 R 25
LI/SS	193 B/202 A2

Dimensions US Standard

Usa code	94028788
TMPH	158
Overall Width (inch)	27.1
Overall Diameter (inch)	68.6
Static Loaded Radius (inch)	30.2
Rolling Circumference (inch)	204.7
Rim Rec	22.00/3.0
Star Rating	**/*
TRA Code	E3/L3
Tread Depth	48

Load capacity (lbs)

mph / psi	58	62	65	69	73	76
30	20900	21500	22700	23400	24700	25400
5	28300	29100	30900	32000	33100	-

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/2/2025 2:17 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..