

EARTHMAX SR 34 - Data Sheet



Description

ARTHMAX SR 34 is an All Steel radial tire specially engineered and designed for rigid dump trucks working in several operations like mining, quarry, logging and haulage. The non-directional block tread pattern provides excellent traction and stability on any type of terrain. EARTHMAX SR 34 is ideal for handling heavy loads. The strong All Steel casing features excellent wear and resistance to any snag and punctures. Its reinforced bead and the shoulder design contribute to an extended tire life-cycle even under the most heavy-duty service conditions.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Rigid Dump Truck

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TMPH
16.00 R 25	CUT RESISTANT COMPOUND	94070749	E3+	***	183 B	11.25/2.0		17.3	59.4	27.3	180.1	TL	130
16.00 R 25	CUT RESISTANT COMPOUND	94070732	E3+	**	177 B	11.25/2.0		17.3	59.4	27.3	180.1	TL	130

Printed on 5/1/2024 1:40 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..