

EARTHMAX SR 35 - Data Sheet



Description

Earthmax SR 35 is a low-profile All Steel radial tire specially designed for articulated dump trucks and wheel loaders. It is ideal for operations requiring exceptional traction and flotation. Earthmax SR 35 provides both excellent traction and stability. Thanks to its strong steel-belted casing, it ensures extraordinary durability and resistance to snags and punctures. The tire is available as cut-resistant compound for a maximum service life even under severe conditions.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Articulated Dump Truck (ADT) • Dozer • Loader

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TMPH
650/65 R 25 (25/65 R 25)	CUT RESISTANT COMPOUND	94058587	E3	**	180 B	19.50/2.5		25	59	26.3	176.9	TL	138
650/65 R 25 (25/65 R 25)	CUT RESISTANT COMPOUND	94058631	E3/L3	***	180 B/193 A2	19.50/2.5		25	59	26.3	176.9	TL	138
650/65 R 25 (25/65 R 25)	CUT RESISTANT COMPOUND	94058624	L3	*	193 A2	19.50/2.5		25	59	26.3	176.9	TL	0
750/65 R 25 (30/65 R 25)	CUT RESISTANT COMPOUND	94051786	E3	**	190 B	24.00/3.0	22.00/3.0,25.00/3.0	29.1	63	28.1	189.1	TL	153
750/65 R 25 (30/65 R 25)	CUT RESISTANT COMPOUND	94053636	E3/L3	***	190 B/202 A2	24.00/3.0	22.00/3.0 ; 25.00/3.0	29.1	63	28.1	189.1	TL	153
750/65 R 25 (30/65 R 25)	CUT RESISTANT COMPOUND	94071340	L3	**	209 A2	24.00/3.0	22.00/3.0,25.00/3.0	29.1	63	28.1	189.1	TL	0
775/65 R 29	CUT RESISTANT COMPOUND	94064410	E3/L3	***	195 B/206 A2	24.00/3.5	24.00/3.0, 25.00/3.5	30.5	69	31	209.1	TL	151
775/65 R 29	CUT RESISTANT COMPOUND	94064427	E3	**	195 B	24.00/3.5	24.00/3.0, 25.00/3.5	30.5	69	31	209.1	TL	151
775/65 R 29	CUT RESISTANT COMPOUND	94064434	L3	*	206 A2	24.00/3.5	24.00/3.0, 25.00/3.5	30.5	69	31	209.1	TL	0
775/65 R 29	CUT RESISTANT COMPOUND	94067589	L3	**	213 A2	24.00/3.5	24.00/3.0, 25.00/3.5	30.5	69	31	209.1	TL	0
875/65 R 29 (35/65 R 29)	CUT RESISTANT COMPOUND	94059812	E3/L3	***	203 B/214 A2	27.00/3.50	27.00/3.0, 28.00/3.5	35	73.2	32.1	218.9	TL	191
875/65 R 29 (35/65 R 29)	CUT RESISTANT COMPOUND	94059805	E3	**	203 B	27.00/3.50	27.00/3.0, 28.00/3.5	35	73.2	32.1	218.9	TL	191
875/65 R 29 (35/65 R 29)	CUT RESISTANT COMPOUND	94059836	L3	*	214 A2	27.00/3.50	27.00/3.0, 28.00/3.5	35	73.2	32.1	218.9	TL	0

Printed on 4/25/2024 7:22 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..