

EARTHMAX SR 41 - Data Sheet



Description

EARTHMAX SR 41 is an All Steel radial tire perfect for Articulated Dump Trucks, Loaders and Dozers. Thanks to its all steel structure and special block pattern, EARTHMAX SR 41 provides excellent resistance against punctures and an extended service life. In addition to long working hours without downtime, the tire ensures extraordinary comfort. EARTHMAX SR 41 is also available in SH-4**** for Low Profile Dump Trucks (LPDT) used in underground haulage operations.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Articulated Dump Truck (ADT) • Dozer • Loader •
Low Profile Dump Truck (LPDT)

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	Tread Depth	TKPH
23.5 R 25	CUT RESISTANT COMPOUND	E4/L4	**/*	185 B/195 A2	19.50/2.5		615	1611	725	4790	TL	53	161
26.5 R 25	CUT RESISTANT COMPOUND	E4/L4	**/*	193 B/202 A2	22.00/3.0		678	1742	775	5150	TL	59	185
26.5 R 25	CUT RESISTANT COMPOUND	SH4	****		22.00/3.0		678	1742	775	5150	TL	59	
26.5 R 25	STANDARD COMPOUND	E4	**	193 B	22.00/3.0		678	1742	775	5150	TL	59	235
29.5 R 25	CUT RESISTANT COMPOUND	E4/L4	**/*	200 B/208 A2	25.00/3.5		761	1861	830	5510	TL	66	225
29.5 R 25	CUT RESISTANT COMPOUND	SH4	****		25.00/3.5		761	1861	830	5510	TL	66	
29.5 R 25	CUT RESISTANT COMPOUND	E4	**	200 B	25.00/3.5		761	1861	830	5510	TL	66	225
29.5 R 25	CUT RESISTANT COMPOUND	L4	***	221 A2	25.00/3.5		761	1861	830	5510	TL	66	
29.5 R 25	STANDARD COMPOUND	E4	**	200 B	25.00/3.5		761	1861	830	5510	TL	66	285
875/65 R 29 (35/65 R 29)	CUT RESISTANT COMPOUND	E4/L4	**/*	203 B/214 A2	27.00/3.50	27.00/3.0, 28.00/3.5	880	1865	837	5680	TL	60	240
875/65 R 29 (35/65 R 29)	CUT RESISTANT COMPOUND	E4	**	203 B	27.00/3.50	27.00/3.0, 28.00/3.5	880	1865	837	5680	TL	60	240
875/65 R 29 (35/65 R 29)	CUT RESISTANT COMPOUND	L4	*	214 A2	27.00/3.50	27.00/3.0, 28.00/3.5	880	1865	837	5680	TL	60	
875/65 R 29 (35/65 R 29)	CUT RESISTANT COMPOUND	L4	**	221 A2	27.00/3.5	27.00/3.0; 28.00/3.5	880	1865	837	5680	TL	60	
35/65 R 33	CUT RESISTANT COMPOUND	SH4	****		28.00/3.5	--	896	2063	926	6283	TL	62	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 8:38 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..