

EARTHMAX SR 431 - Technical Specifications



Description

EARTHMAX SR 431 (E-4) is an All Steel tire specially designed for rigid haul trucks operating in severe mining conditions (surface and underground mines). The non-directional tread pattern ensures excellent traction and stability. The tire features a strong All Steel casing and a special tread compound providing extraordinary cut and chip resistance as well as a long service life even in rocky, abrasive and harsh environments.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Rigid Dump Truck

| | |
|-----------|------------------------|
| Version | CUT RESISTANT COMPOUND |
| Type | TL |
| Tyre Size | 18.00 R 25 |
| LI/SS | 185 B |

Dimensions US Standard

| | |
|------------------------------|-----------|
| Usa code | 94060788 |
| TMPH | 96 |
| Overall Width (inch) | 20.5 |
| Overall Diameter (inch) | 65.4 |
| Static Loaded Radius (inch) | 29.9 |
| Rolling Circumference (inch) | 198.4 |
| Rim Rec | 13.00/2.5 |
| Star Rating | ** |
| TRA Code | E4 |

Load capacity (lbs)

| mph / psi | 73 | 76 | 80 | 83 | 87 | 91 | 94 | 98 | 102 |
|-----------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30 | 16100 | 16500 | 17100 | 17600 | 18200 | 18700 | 19300 | 19800 | 20400 |

Printed on 4/25/2024 11:48 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..