



## EARTHMAX SR 45 PLUS - Data Sheet

### Description

EARTHMAX SR 45 PLUS is an All Steel radial tire specially designed for rigid haul trucks. It is ideal for operations in long hauls. The tread pattern of the EARTHMAX SR 45 PLUS minimizes vibration and noise.



### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Rigid Dump Truck

| SIZE       | Version                 | USACode  | TRA Code | Star R | LI/SS | RIM REC   | RIM ALT | OW   | OD    | SLR  | RC    | Type | TMPH |
|------------|-------------------------|----------|----------|--------|-------|-----------|---------|------|-------|------|-------|------|------|
| 27.00 R 49 | CUT RESISTANT COMPOUND  | 94045655 | E4       | **     | 223 B | 19.50/4.0 | --      | 29.4 | 106.4 | 47.8 | 318.7 | TL   | 301  |
| 27.00 R 49 | HEAT RESISTANT COMPOUND | 94049813 | E4       | **     | 223 B | 19.50/4.0 | --      | 29.4 | 106.4 | 47.8 | 318.7 | TL   | 448  |
| 27.00 R 49 | STANDARD COMPOUND       | 94049806 | E4       | **     | 223 B | 19.50/4.0 | --      | 29.4 | 106.4 | 47.8 | 318.7 | TL   | 370  |
| 33.00 R 51 | CUT RESISTANT COMPOUND  | 94073306 | E4       | **     | 235 B | 24.00/5.0 |         | 35.8 | 120.7 | 53.9 | 366.7 | TL   | 414  |
| 33.00 R 51 | HEAT RESISTANT COMPOUND | 94073320 | E4       | **     | 235 B | 24.00/5.0 |         | 35.8 | 120.7 | 53.9 | 366.7 | TL   | 558  |
| 33.00 R 51 | STANDARD COMPOUND       | 94073313 | E4       | **     | 235 B | 24.00/5.0 |         | 35.8 | 120.7 | 53.9 | 366.7 | TL   | 483  |

Printed on 4/26/2024 5:11 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..