

EARTHMAX SR 468 - Technical Specifications



Description

EARTHMAX SR 468 is an All Steel radial tire specially designed for rigid haul trucks. Its unique tread design with special tread compounds makes it perfect for hard, rocky and tough mining conditions. Its tread lug blocks with circumferential grooves and intertwined blocks ensures effective heat dissipation. Also, the sturdy square shoulder assist in ejecting loose stones to protect the tire from injury. EARTHMAX SR 468 is developed using BKT's cutting-edge technology to carry heavy loads, deliver longer service life and provide resistance to rock cuts and punctures.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Rigid Dump Truck

Version	STANDARD COMPOUND
Type	TL
Tyre Size	50/80 R 57
LI/SS	257 B

Dimensions International Standard

TKPH	1130
Overall Width (mm)	1205
Overall Diameter (mm)	3610
Static Loaded Radius (mm)	1597
Rolling Circumference (mm)	10870
Rim Rec	32.00/6.0
Rim Alt	29.00/6.0
Star Rating	**
TRA Code	E4

Load capacity (Kg)

km/h / bar	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	61500	63000	65000	67000	69000	71000	73000

Printed on 4/29/2024 2:04 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..