

EARTHMAX SR 47 - Technical Specifications



Description

EARTHMAX SR 47 (E-4) is an **All Steel** radial tire specially designed for rigid haul trucks operating in conditions requiring maximum rock cut and puncture resistance. The E-4 tread depth and the unique tread design ensure long wear even on long hauls, thus reducing downtime and increasing productivity. Available in standard and cut-resistant compounds.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Rigid Dump Truck

Version	STANDARD COMPOUND
Type	TL
Tyre Size	18.00 R 33
LI/SS	195 B

Dimensions US Standard

Usa code	94064472
TMPH	140
Overall Width (inch)	20.1
Overall Diameter (inch)	74.2
Static Loaded Radius (inch)	34.1
Rolling Circumference (inch)	223.4
Rim Rec	13.00/2.5
Star Rating	***
TRA Code	E4

Load capacity (lbs)

mph / psi	105	109	112	116
30	24700	25400	26000	26800

Printed on 4/26/2024 6:23 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..