



EARTHMAX SR 50 - Data Sheet

Description

EARTHMAX SR 50 (L-5) is an **All Steel** radial tire specially designed for loaders. The durable casing and sidewall protectors are ideal for the most demanding operations. EARTHMAX SR 50 is made of a special cut-resistant compound which ensures a long wear life. Operators will also appreciate its excellent traction, stability and comfortable ride.



UM

International Standard

Construction

 RADIAL

Machinery

OTR: Loader

| SIZE | Version | TRA Code | Star R | LI/SS | RIM REC | RIM ALT | OW | OD | SLR | RC | Type |
|-----------|------------------------|----------|--------|--------|-----------|---------|-----|------|-----|------|------|
| 26.5 R 25 | CUT RESISTANT COMPOUND | L5 | * | 202 A2 | 22.00/3.0 | | 690 | 1772 | 806 | 5334 | TL |
| 26.5 R 25 | CUT RESISTANT COMPOUND | L5 | ** | 209 A2 | 22.00/3.0 | | 690 | 1772 | 806 | 5334 | TL |
| 29.5 R 25 | CUT RESISTANT COMPOUND | L5 | * | 208 A2 | 25.00/3.5 | | 775 | 1901 | 862 | 5722 | TL |
| 29.5 R 25 | CUT RESISTANT COMPOUND | L5 | ** | 216 A2 | 25.00/3.5 | | 775 | 1901 | 862 | 5722 | TL |

Printed on 4/20/2024 6:14 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..