



## EARTHMAX SR 53 - Data Sheet



### Description

EARTHMAX SR 53 is an All Steel radial tire specially designed for loaders, dozers and low profile dump trucks (LPDT) operating in severe rocky conditions, including underground operations and scrap yards. The deep L-5 tread and the cut-resistant compound provide an extended wear life in addition to excellent traction and stability.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Dozer • Loader • Low Profile Dump Truck (LPDT)

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
17.5 R 25	CUT RESISTANT COMPOUND	94045808	L5	*	176 A2	14.00/1.5		17.1	55.1	25.1	165.9	TL
17.5 R 25	CUT RESISTANT COMPOUND	94058945	L5	**	182 A2	14.00/1.5		17.1	55.1	25.1	165.9	TL
17.5 R 25	CUT RESISTANT COMPOUND	94064021	L5	***	188 A2	14.00/1.5		17.1	55.1	25.1	165.9	TL
17.5 R 25	CUT RESISTANT COMPOUND (UMS)	94058952	L5	**		14.00/1.5		17.1	55.1	25.1	165.9	TL
20.5 R 25	CUT RESISTANT COMPOUND	94044306	L5	*	186 A2	17.00/2.0		21.1	61	27.8	183.7	TL
23.5 R 25	CUT RESISTANT COMPOUND	94045839	L5	*	195 A2	19.50/2.5		23.8	65.6	29.8	197.4	TL
23.5 R 25	CUT RESISTANT COMPOUND	94062362	L5	**	201 A2	19.50/2.5		23.8	65.6	29.8	197.4	TL
23.5 R 25	CUT RESISTANT COMPOUND (UMS)	94070411	L5	**		19.50/2.5		23.8	65.6	29.8	197.4	TL
26.5 R 25	CUT RESISTANT COMPOUND	94049103	L5	*	202 A2	22.00/3.0		26.8	70.4	31.5	211.7	TL
26.5 R 25	CUT RESISTANT COMPOUND	94057153	L5	**	209 A2	22.00/3.0		26.8	70.4	31.5	211.7	TL
26.5 R 25	CUT RESISTANT COMPOUND	94065516	L5	***	214 A2	22.00/3.0		26.8	70.4	31.5	211.7	TL
26.5 R 25	CUT RESISTANT COMPOUND (UMS)	94055050	L5	**		22.00/3.0		26.8	70.4	31.5	211.7	TL
29.5 R 25	CUT RESISTANT COMPOUND	94049301	L5	*	208 A2	25.00/3.5		30.3	75.3	33.8	226.6	TL
29.5 R 25	CUT RESISTANT COMPOUND	94055630	L5	**	216 A2	25.00/3.5		30.3	75.3	33.8	226.6	TL
29.5 R 25	CUT RESISTANT COMPOUND (UMS)	94055067	L5	**		25.00/3.5		30.3	75.3	33.8	226.6	TL
29.5 R 29	CUT RESISTANT COMPOUND	94067206	L5	**	218 A2	25.00/3.5	24.00/3.5	29.7	79.3	35.6	238.5	TL
29.5 R 29	CUT RESISTANT COMPOUND	94069590	L5	***	223 A2	25.00/3.5	24.00/3.5	29.7	79.3	35.6	238.5	TL
29.5 R 29	CUT RESISTANT COMPOUND (UMS)	94069309	L5	**		25.00/3.5	24.00/3.5	29.7	79.3	35.6	238.5	TL
35/65 R 33	CUT RESISTANT COMPOUND	94055036	L5	**	224 A2	28.00/3.5	-	35.8	81.2	36	244.7	TL
35/65 R 33	CUT RESISTANT COMPOUND	94058594	L5	***	229 A2	28.00/3.5		35.8	81.2	36	244.7	TL
35/65 R 33	CUT RESISTANT COMPOUND (UMS)	94055043	L5	**		28.00/3.5		35.8	81.2	36	244.7	TL
45/65 R 39	CUT RESISTANT COMPOUND	94067305	L5	**	242 A2	36.00/4.5	32.00/4.5	43.3	101.5	44	305	TL
45/65 R 45	CUT RESISTANT COMPOUND	94053575	L5	**	245 A2	36.00/4.5		44.3	107.5	47.7	323.8	TL
45/65 R 45	CUT RESISTANT COMPOUND	94073078	L5	***	250 A2	36.00/4.5		44.3	107.5	47.7	323.8	TL
50/65 R 51	CUT RESISTANT COMPOUND	94068913	L5	**	253 A2	40.00/4.5		48.8	121.7	54	366.5	TL
60/80 R 57	CUT RESISTANT COMPOUND	94075218	L5	**	274 A2	47.00/5.0	47.00/6.0	59.6	154.7	68.6	466.1	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/13/2024 6:49 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..