

# EARTHMAX SR 57 - Technical Specifications



## Description

EARTHMAX SR 57 is an All Steel radial tire specially engineered for loaders, dozers and utility vehicles operating in underground mines. The tire provides superior traction, stability and comfort on severe and rocky surfaces. The L-5 extra deep tread and the specially formulated UMS (underground mine service) compound provide a longer tread wear in addition to extraordinary resistance to rock cuts, and punctures.

## UM

International Standard

## Construction

 RADIAL

## Machinery

OTR: Dozer • Load Haul Dump (LHD) • Loader

Version	CUT RESISTANT COMPOUND
Type	TT
Tyre Size	10.00 R 15

## Dimensions International Standard

Overall Width (mm)	278
Overall Diameter (mm)	916
Rim Rec	7.50
Rim Alt	7.00
Star Rating	*
TRA Code	L5
Tread Depth	48

## Load capacity (Kg)

km/h / bar	7.00
6.00	3500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/11/2025 2:59 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..