



EM 936 - Data Sheet



Description

EM 936 has been specially designed for excavators and telehandlers in digging and loading operations. Besides, one size is particularly suitable for graders and loaders in grading, loading and transport applications. EM 936 features outstanding riding comfort and enhanced self-cleaning properties. It also ensures a high level of handling comfort and provides excellent traction even under heavy-duty service conditions. Its "special" version is made of a special compound.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Excavator • Telehandler

| SIZE | Version | TRA Code | LI/SS | PR | RIM REC | RIM ALT | OW | OD | SLR | RC | Type |
|--------------------------------|-----------|----------|--------------|----|-------------|-----------|-----|------|-----|------|------|
| 10.00 - 20 | SPECIAL | E2 | 146 B | 16 | 7.5 | 7.0 ; 8.0 | 275 | 1050 | 498 | 3180 | TT |
| 10.00 - 20 | STANDARD | E2 | 146 B | 16 | 7.5 | 7.0 ; 8.0 | 275 | 1050 | 498 | 3180 | TT |
| 11.00 - 20 | STANDARD | E2 | 149 B | 16 | 8.0 | 7.5 ; 8.5 | 300 | 1110 | 508 | 3302 | TT |
| 12.5 - 20 | STANDARD | E2 | | 12 | 11.0 | | 330 | 1035 | 464 | 3210 | TT |
| 16.0/70 - 20 (400 / 70 -20) | SPECIAL | E2 | 152 B/168 A2 | 16 | 13 SDC | 13 | 405 | 1090 | 480 | 3295 | TL |
| 16.0/70 - 20 (400 / 70 -20) | SPECIAL | E2 | 149 B/166 A2 | 14 | 13 SDC | 13 | 405 | 1090 | 480 | 3295 | TT |
| 16.0/70 - 20 (400 / 70 -20) | SPECIAL | E2 | 149 B/166 A2 | 14 | 13 SDC | 13 | 405 | 1090 | 480 | 3295 | TL |
| 16.0/70 - 20 (400 / 70 -20) | STANDARD | E2 | 149 B/166 A2 | 14 | 13 SDC | 13 | 405 | 1090 | 480 | 3295 | TL |
| 8.25 - 20 | STANDARD | E2 | 133 B | 14 | 6.5 | 6.0 ; 7.0 | 235 | 980 | 467 | 2970 | TT |
| 9.00 - 20 | SPECIAL | E2 | 140 B | 14 | 7.0 | 6.5 ; 7.5 | 256 | 1012 | 481 | 3070 | TT |
| 9.00 - 20 | STANDARD | E2 | 140 B | 14 | 7.0 | 6.5 ; 7.5 | 256 | 1012 | 481 | 3070 | TT |
| 16.0/70 - 24 (405/70 - 24) | STANDARD | E2 | 152 B/169 A2 | 14 | 13 SDC | 13 (DC) | 404 | 1170 | 575 | 3600 | TL |
| 16.0/70 - 24 (405/70 - 24) | STANDARD | E2 | 143 B/162 A2 | 10 | 13 SDC | 13 (DC) | 404 | 1170 | 575 | 3600 | TL |
| 20 - 24 (22/70 - 24) | STANDARD | E2/G2/L2 | 158 B/173 A2 | 12 | 16.00 T SDC | | 535 | 1390 | 665 | 4205 | TL |
| 17.5 - 25 | DUAL BEAD | E2/L2 | | 24 | 14.00/1.5 | | 450 | 1340 | 600 | 4060 | TL |

Printed on 12/11/2023 12:49 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..