

EM 937 IND3 (ECH) - Technical Specifications



Description

EM 937 (E-3) IND is specially designed for empty-containerhandling operations in stacking and loading applications. It features excellent durability and a long tire life. EM 937 (E-3) IND is ideal on paved surfaces and for all operations requiring a high level of handling in the port. *For size 14.00-24 please confirm service rim or consult manufacturer/distributor

UM

US Standard

Construction

🐼 BIAS

Machinery

Industrial: Empty Container Handler

Version	PORT INDUSTRIAL
Туре	TL
Tyre Size	14.00 - 24

Dimensions US Standard

Usa code	94043996
Ply Rating	28
Overall Width (inch)	14.8
Overall Diameter (inch)	53.9
Static Loaded Radius (inch)	24.7
Rolling Circumference (inch)	159.4
Rim Rec	10.00 WA
Rim Alt	10.00 VA
TRA Code	IND3

Load capacity (lbs)

mph / psi	145
5	29750

Printed on 4/27/2024 10:35 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..