

## FARM 2000 - Technical Specifications



### Description

The FARM 2000 tire is suitable on tractors for soil tillage applications. It has been designed with a special cut-and-chip resistant compound to ensure better durability. Thanks to its strong casing, FARM 2000 offers high load capacity. It also provides great traction and self-cleaning properties.

### UM

International Standard

### Construction

✚ BIAS

### Machinery

Agriculture: Tractor

Version	STANDARD
Type	TL
Tyre Size	260/70 - 15.3
LI/SS DRIVE WHEEL	114 A8
LI/SS FREE ROLLING	126 A8

## Dimensions International Standard

Section Width (mm)	265
Overall Diameter (mm)	775
Static Loaded Radius (mm)	349
Rolling Circumference (mm)	2294
SRI (mm)	360
Rim Rec	9.00
ECE	E11-106R-003516

## Load capacity (Kg)

km/h / bar	3.60
10 FR	2380
25 FR	2025
30 FR	1905
40 FR	1700
10 DW	1650
25 DW	1405
30 DW	1320
40 DW	1180

Printed on 4/29/2024 9:45 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..