

FARM HIGHWAY TOUGH - Data Sheet



Description

FARM HIGHWAY TOUGH is a high-speed tire designed for transport and soil tillage applications with trailers and implement machinery. It provides high load capacity also at high speeds and ensures a long tire life-cycle.

UM

International Standard

Construction

❖ BIAS

Machinery

Agriculture: Implement Machinery • Trailer

SIZE	Version	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
10.00 - 15 FI	STANDARD	128 J	8	8 LB		274	853	0	0	TL	E11-54R-0017870
11L - 15 FI	STANDARD	128 J	12	8 LB	10 LB ; 8 J	279	777	347	2214	TL	E11-54R-0017871
11L - 15 FI	STANDARD	120 J	8	8 LB	10 LB ; 8 J	279	777	347	2214	TL	E11-54R-0018902
12.5L - 15 FI	STANDARD	134 J	12	10 LB		317	815	362	2323	TL	E11-54R-0019049
9.5L - 15 FI	STANDARD		12	7.00	8 LB	245	766	343	2183	TL	
9.5L - 15 FI	STANDARD		8	7.00	8 LB	245	766	343	2183	TL	

Printed on 5/8/2024 2:35 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..